

## **Industrial LCD Monitor**

### **Features:**

- ⊕ *High Contrast color TFT LCD Display support resolution up to SVGA.*
- ⊕ *Power management system conforms to VESA DPMS and EPA Energy star standards.*
- ⊕ *Full consideration for touch screen installation and application.*
- ⊕ *Universal Power adapter*
- ⊕ *Support DDC1 & DDC2B for Plug & Play compatibility.*
- ⊕ *Advanced OSD control for picture quality adjustment.*
- ⊕ *Detachable stand for wall-mounting application.*
- ⊕ *Open type with metal frame.*
- ⊕ *Custom design by request.*



**Model : W0-J104S00-A**



**WiseTac Co., Ltd**

*Specifications*

<b>Model Name</b>	<b>WO-J104S00-A</b>
Panel Type	AUO 10.4-inch LCD Panel
Active Display Area (mm)	211.2 (H) x 158.4 (V)
Pixel Pitch (mm)	0.264 (H) x 0.264 (V)
Number of Pixels	800*600
Contrast Ratio	700 : 1
Display Color	16.2M / 262K colors
Brightness (cd/m <sup>2</sup> )	400 cd/m <sup>2</sup>
Backlight	LED Backlight
Viewing Angle (CR=10)	-80~ +80 (H) ; -60 ~ +80 (V)
Optical Rise Time/Fall Time	60 ms
Synchronization Range Horizontal / Vertical	31.5 ~ 68 KHz / 56 ~ 75 Hz
Recommended Resolution	800 x 600 @ 60Hz, 75Hz
Signal Connector	15 pin D-Sub
Front Control	Power ON / OFF with LED, Menu & Select / Up & value decrease Auto Adjust / Down / value increase / Source
OSD	Volume, Brightness, Contrast, Color-RGB, Auto Tune, H-Position, V-Position, Center, Frequency, Phase, Track, Text, / Graphics, Language, Recall, Save, Saturation, Hue,
Power Board	Universal AC 100V ~ 240V, 50 ~ 60Hz Input DC 12V, 4.16A Output, 50Watt MAX
Power Management	VESA DPMS Compliant
Plug & Play	Support DDC1&DDC2B for Plug & Play compatibility
Option Touch	Resistive ; Capacitive
Video Input	Option